

Dräger PARAT® 4500 Industrial Escape Hood

Where hazardous substances exist in your workplace, you can never entirely rule out the possibility of these substances leaking out into the air. However, with the correct safety precautions, including the use of the Dräger PARAT® 4500, you can escape safely.



Equipped with a highly efficient combination filter the Dräger PARAT 4500 Industrial Escape Hoods give you a minimum of 15 minutes escape protection against toxic industrial gases, fumes, and particles – helping you to escape to safety.

The Dräger PARAT 4500 hood protects the entire head from toxic gases and dusts and ensures a safe escape also for bearded users and spectacle wearers.

In an escape situation there is no time for blurred vision. The Dräger PARAT 4500's wide, anti-fog coated visor keeps vision clear during an escape.

According to your application you can choose from three different packaging options of the Dräger PARAT 4500:

the soft pack easy to carry along, the traveller pack in a well-protected plastic case and the heavy-duty box tried and tested in heavy industry.

Benefits:

- Highly visible hood in a universal size with a flexible neck seal
- Wide, anti-fog coated visor for a clear view during an escape
- Highly efficient ABEK-P15 filter: protects from toxic industrial gases, fumes and particles
- Three different packaging variations the right option for every environment



Dräger PARAT® 4500: Industrial escape hood



Dräger PARAT® 4520: Soft-Pack version

TECHNICAL DATA

Filter performance:	Combination cartridge (gas & particle filter) provides protection against organic and inorganic gases and particles, Filter Type ABEK-P15 approved in accordance to DIN 58647 Part 7		
Approved duration:	minimum 15 minutes		
Service Life:	12 years total (4 years maintenance free – thereafter filter change every 4 years)		
Weight:	approx. 600 grams		
Dimensions:	Dräger PARAT 4520 Soft-Pack & Dräger PARAT 4530 Traveller-Pack:		
	8 x 19 x 13,5 cm (H x L x W)		
	Dräger PARAT 4560 Box:		
	18 x 19 x 8 cm (H x L x W)		
Approval:	val: Approved in accordance to DIN 58647 Part 7 (CE mark 0158)		
Particle filtration efficiency:	in accordance with EN143:2000 (P2)		

Filter capacity according to DIN 58647-7*

Туре	Test gas	Concentration in ml/m ³	Breakthrough in ml/m ³	Minimum breakthrough time in min
A	Cyclohexane (C ₆ H ₁₂)	2,500	10	15
В	Chlorine (Cl ₂)	2,500	0.5	15
В	Hydrogen sulphide (H ₂ S)	2,500	10	15
В	Hydrogen cyanide (HCN)	2,500	10	15
E	Sulphur dioxide (SO ₂)	2,500	5	15
K	Ammonia (NH ₃)	2,500	25	15
В	Hydrogen sulphide (H ₂ S)	10,000*)	20	5

^{*} Test conditions according to DIN 58647-7: 30 L/min, 70% relative humidity, 20°C.

ORDER INFORMATION

Dräger PARAT 4520 Soft-Pack, in a handy travel case	R 57 977
Dräger PARAT 4530 Traveller-Pack, in a plastic case	R 57 979
Dräger PARAT 4560 Box	R 57 980
Dräger PARAT Training hood	R 54 105
Spare parts kit Dräger PARAT 4500 (includes ABEK-P15 replacement filter and exhalation valve)	R 57 978
Wall holder for Dräger PARAT 4530 Traveller-Pack	R 51 906
Carrying harness for Dräger PARAT 4500 Traveller-Pack and Soft-Pack	R 53 205
Shoulder strap to go with harness (R 53 205)	R 53 783
Waist belt for use with carrying harness (R 53 205)	R 53 026
Hip belt for use with Dräger PARAT 4560 Box	67 33 934

HEADQUARTERS

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882-0 Fax +49 451 882-2080 nbc@draeger.com

www.draeger.com/defense

SUBSIDIARIES

AUSTRALIA Draeger Safety Pacific Pty. Ltd. Axxess Corporate Park Unit 99, 45 Gilby Road Mt. Waverley Vic 3149 Tel +61 3 92 65 50 00

Fax +61 3 92 65 50 95

P. R. CHINA

Beijing Fortune Draeger Safety Equipment Co., Ltd. A22 Yu An Rd, B Area, Tianzhu Airport Industrial Zone, Shunyi District, Beijing 101300

Tel +86 10 80 49 80 00 Fax +86 10 80 49 80 05

FRANCE

Dräger Safety France SAS 3c route de la Fédération, BP 80141 67025 Strasbourg Cedex 1 Tel +33 3 88 40 59 29 Fax +33 3 88 40 76 67

NETHERLANDS

Dräger Safety Nederland B.V. Edisonstraat 53 2700 AH Zoetermeer Tel +31 79 344 46 66 Fax +31 79 344 47 90

SINGAPORE

Draeger Safety Asia Pte Ltd 67 Ayer Rajah Crescent #06-03 Singapore 139950 Tel +65 68 72 92 88 Fax +65 65 12 19 08

REP. OF SOUTH AFRICA Dräger South Africa

(Pty) Ltd. P.O.Box 68601 Bryanston 2021 Tel +27 11 465 99 59 Fax +27 11 465 69 53

SPAIN

Draeger Safety Hispania S.A. Calle Xaudaró 5 28034 Madrid Tel +34 91 728 34 00 Fax +34 91 729 48 99

UNITED KINGDOM

Draeger Safety UK Ltd. Blyth Riverside Business Park, Blyth, Northumberland NE24 4RG Tel +44 1670 352 891 Fax +44 1670 356 266

^{*)} To determine the breakthrough capacity of the gas filter it is additionally tested with 10,000 ml/m³ hydrogen sulphide.